

SG4 Safety Light Curtain

Price -30%



High reliability
Easy installation and alignment
Cost effective

SG4 Safety Light Curtain

Technical Data:

- Type 4 (IEC 61496), SIL3 (IEC 61508), PL e (EN ISO 13849)
- Finger and hand detection
- Resolution 14 and 30 mm
- Monitored height 150...1800 mm (with 150 mm steps)
- Up to 19 m operating distance
- Compact dimensions (32,3 × 36,9 mm section)
- Rotating and anti-vibration brackets
- IP65 Protection; IP69K with optional tube

Price -30%

Applications:

- Automatic machines: cutting, packaging, material handling and storing
- Automatic and semi-automatic assembling lines
- Milling, lathe and shearing machines
- Bending and metal-working machines



SG 4 - 30 - 015 - 00 - E

Type		Resolution		Monitored height		Version	
4	Type 4	14	Finger 14 mm	15	150 mm	E	Type 4, EDM, Coded
		30	Hand 30 mm	30	300 mm	X	Basic Function
				...	...		
				180	1 800 mm		

STOCK TYPES



Selected types in stock

Type	ArtNo	Resolution mm	Height mm	Operating Distance m	EUR/pcs	Special offer EUR/pcs
SG4-14-030-00-E	957901010	14	300	6	881,00	616,70
SG4-14-045-00-E	957901020	14	450	6	1 087,00	760,90
SG4-14-060-00-E	957901030	14	600	6	1 295,00	906,50
CS-A1-02-U-05	95ASE1130	4-poles connector M12 axial, for emitter, 5 m cable			13,30	9,31
CS-A1-06-U-05	95ASE1230	8-poles connector M12 axial, for receiver, 5 m cable			29,46	20,62
SE-SR2	95ACC6170	Safety relay, 3 NO + 1 NC, selectable auto/manual restart			220,40	154,28